

platen

warmgewalst, onbehandeld

leveringsvoorwaarden: NEN-EN 10025-1 en -2
 toleranties: NEN-EN 10029 (voor $t \geq 3$ mm);
 NEN-EN 10051 (voor $t < 3$ mm)



t mm	G ₈ (kg/plaat)							G ₈ (kg/plaat)							t mm
	ℓ x b	2000 x 1000	2500 x 1250	3000 x 1500	6000 x 1000	6000 x 1250	6000 x 1500	6000 x 1800	6000 x 2000	8000 x 2500	10000 x 3000	12000 x 2000	12000 x 2500	12000 x 3000	
1,5		24,0	37,5	54,0											1,5
2		32,0	50,0	72,0											2
2,5		40,0	62,5	90,0											2,5
3		48,0	75,0	108	144	180	216	259	288						3
4		64,0	100	144	192	240	288	346	384						4
5		80,0	125	180	240	300	360	432	480						5
6		96,0	150	216	288	360	432	518	576						6
8		128	200	288	384	480	576	691	768					2304	8
10		160	250	360	480	600	720	864	960			1920	2400	2880	10
12		192	300	432	576	720	864	1037	1152			2304	2880	3456	12
15		240	375	540	720	900	1080	1296	1440			2880	3600	4320	15
20		320	500	720	960	1200	1440	1728	1920	3200		3840	4800	5760	20
25		400	625	900	1200	1500	1800	2160	2400	4000		4800	6000	7200	25
30		480		1080								5760			30
35		560													35
40		640									9600				40
45		720													45
50		800													50
60		960													60
70		1120													70
80		1280													80
90		1440													90
100		1600													100