


## balkstaal

## breedflensbalken, HEM

leveringsvoorwaarden: NEN-EN 10025-1 en -2  
 toleranties: NEN-EN 10034; DIN 1025/4  
 max. handelslengte: 25 m



profiel nr.	G <sub>8</sub> kg/m	A mm <sup>2</sup>	h mm	b mm	t <sub>w</sub> mm	t <sub>f</sub> mm	A <sub>L</sub> m <sup>2</sup> /m	I <sub>y</sub> x10 <sup>4</sup> mm <sup>4</sup>	W <sub>y,rel</sub> x10 <sup>3</sup> mm <sup>3</sup>	I <sub>z</sub> x10 <sup>4</sup> mm <sup>4</sup>	W <sub>z,rel</sub> x10 <sup>3</sup> mm <sup>3</sup>	profiel nr.
100	42,6	5324	120	106	12	20	0,619	1143	190	399	75,3	100
120	53,1	6641	140	126	12,5	21	0,738	2018	288	703	112	120
140	64,4	8056	160	146	13	22	0,857	3291	411	1144	157	140
160	77,6	9705	180	166	14	23	0,970	5098	566	1759	212	160
180	90,6	11325	200	186	14,5	24	1,09	7483	748	2580	277	180
200	105	13128	220	206	15	25	1,20	10642	967	3651	354	200
220	120	14944	240	226	15,5	26	1,32	14605	1217	5012	444	220
240	160	19959	270	248	18	32	1,46	24290	1799	8153	657	240
260	176	21964	290	268	18	32,5	1,57	31307	2159	10449	780	260
280	192	24016	310	288	18,5	33	1,69	39547	2551	13163	914	280
300	242	30308	340	310	21	39	1,83	59201	3482	19403	1252	300
320	250	31205	359	309	21	40	1,87	68135	3796	19709	1276	320
340	253	31583	377	309	21	40	1,90	76372	4052	19711	1276	330
360	255	31881	395	308	21	40	1,93	84867	4297	19522	1268	460
400	261	32578	432	307	21	40	2,00	104119	4820	19335	1260	400
450	268	33544	478	307	21	40	2,10	131484	5501	19339	1260	450
500	275	34430	524	306	21	40	2,18	161929	6180	19155	1252	500
550	284	35438	572	306	21	40	2,28	197984	6923	19158	1252	550
600	291	36366	620	305	21	40	2,37	237448	7660	18975	1244	600
650	299	37374	668	305	21	40	2,47	281668	8433	18979	1245	650
700	306	38302	716	304	21	40	2,56	329278	9198	18797	1237	700
800	323	40427	814	303	21	40	2,75	442598	10875	18627	1230	800
900	339	42363	910	302	21	40	2,93	570434	12537	18452	1222	900
1000	355	44421	1008	302	21	40	3,13	722299	14331	18459	1222	1000